

**IN THE CLAIMS**

Please cancel claim 19 without prejudice or disclaimer and please rewrite the claims as shown below.

C 1. (Currently Amended) An array of photodiodes made of regions of a second conductivity type formed in a semiconductive region of a first conductivity type, divided into three interleaved sub-arrays, each sub-array corresponding to a respective color of light, all photodiodes of a ~~same~~ respective sub-array being coated with a same interference filter including at least one insulating layer of determined thickness coated with at least one conductive layer, the determined thickness of said at least one insulating layer and said at least one conductive layer coating the respective sub-array determining the respective color of light that is interferentially filtered and provided to the respective sub-array, wherein said at least one conductive layer is electrically connected to the semiconductive region of the first conductivity type.

2. (Original) The array of photodiodes of claim 1, wherein the electric connection is indirect.

3. (Original) The array of photodiodes of claim 1, wherein the semiconductor substrate is a single-crystal silicon substrate, and the interference filter includes a silicon oxide layer formed above the substrate and a conductive polysilicon layer formed above the silicon oxide layer.

4. (Previously Amended) The array of photodiodes of claim 1, wherein the semiconductive region of the first conductivity type comprises a semiconductor substrate made of single-crystal silicon.

5. (Original) The array of photodiodes of claim 1, wherein said at least one insulating layer comprises a silicon oxide layer.

6. (Currently Amended) The array of photodiodes of claim 1, wherein said at least one conductive layer comprises a polysilicon layer.

7. (Currently Amended) The array of photodiodes of claim 1, further comprising a silicon nitride layer over said at least one conductive layer.

8. (Currently Amended) The array of photodiodes of claim 1, wherein said semiconductive region of the first conductivity type comprises a semiconductor substrate made of single-crystal silicon, said at least one insulating layer comprises a silicon oxide layer, and said at least one conductive layer comprises a polysilicon layer.

9. (Currently Amended) The array of photodiodes of claim 8, further comprising a silicon nitride layer over said at least one conductive layer.

10. (Previously Amended) The array of photodiodes of claim 9, wherein said single-crystal silicon layer and said polysilicon layer have a high refraction coefficient on the order of 4, while said silicon oxide layer and silicon nitride layer have a lower refraction coefficient, on the order of 1.5.

11. (Currently Amended) The array of photodiodes of claim 1, wherein said at least one conductive layer is connected to said semiconductive region of the first conductivity type at a heavily doped P-type region thereof.

12. (Currently Amended) A photodiode comprising:  
a semiconductor substrate of a first conductivity type;  
a semiconductive region of a second conductivity type formed in said semiconductor substrate;  
a multilayer interference filter disposed over said semiconductive region and including;  
at least one insulating layer ~~of~~ having a predetermined thickness, and  
a conductive layer disposed over said at least one insulating layer,

wherein said conductive layer includes a conductive portion that electrically connects said conductive layer to said semiconductor substrate of the first conductivity type, and wherein the predetermined thickness of said at least one insulating layer, in combination with said conductive layer, is adapted to interferentially filter a particular wavelength of light.

13. (Original) The photodiode of claim 12, wherein said semiconductor substrate comprises a single-crystal silicon.

Cont'd  
C1  
14. (Original) The photodiode of claim 13, wherein said at least one said insulating layer comprises a silicon oxide layer.

15. (Original) The photodiode of claim 14, wherein said conductive layer comprises a polysilicon layer.

16. (Original) The photodiode of claim 15, further comprising a silicon nitride layer over said conductive layer.

17. (Currently Amended) A photodiode comprising:  
a semiconductor substrate of a first conductivity type;  
a semiconductive region of a second conductivity type formed in said semiconductor substrate;  
a multilayer interference filter disposed over said semiconductive region and including;  
at least one insulating layer ~~of~~ having a predetermined thickness, and  
a conductive layer disposed over said at least one insulating layer, and  
means defining a conductive portion that electrically connects said conductive layer to said semiconductor substrate of the first conductivity type,  
wherein the predetermined thickness of said at least one insulating layer, in combination with said conductive layer, is adapted to interferentially filter a particular wavelength of light.

18. (Original) The photodiode of claim 17, further including means defining a heavily doped region of said semiconductor substrate to which said conductive portion couples.

19-26. (Canceled)

27. (Currently Amended) A photodiode comprising:  
a semiconductor substrate of a first conductivity type;  
a semiconductive region of a second conductivity type formed in said semiconductor substrate;  
a multilayer interference filter disposed over said semiconductive region and including:  
at least one insulating layer ~~of~~ having a predetermined thickness, and  
a conductive layer disposed over said at least one insulating layer,  
said semiconductor substrate defining a well formed in a base substrate of the second conductivity type, said conductive layer being electrically connected to said base substrate,  
wherein the predetermined thickness of said at least one insulating layer, in combination with said conductive layer, is adapted to interferentially filter a particular wavelength of light.

28. (Currently Amended) The array of photodiodes of claim 1, wherein the at least one insulating layer includes a first insulating layer and a second insulating layer disposed below the first insulating layer, the first insulating layer extending across ~~all the~~ three photodiodes ~~of the same sub-array~~ each in a different one of the three interleaved sub-arrays, and the second insulating layer extending across at least two photodiodes of the ~~same sub-array~~ three photodiodes, wherein said at least one conductive layer extends across each of all the three photodiodes ~~of the same sub-array~~ above the first insulating layer.

29. (Currently Amended) The array of photodiodes of claim 28, wherein the at least one insulating layer further includes a third insulating layer, disposed below the second insulating layer, that extends ~~only across a single photodiode of the same sub-array~~ only one of the three photodiodes.

30. (Currently Amended) The array of photodiodes of claim 1, wherein ~~each sub-array includes a plurality of respective photodiodes~~ said at least one insulating layer extends across three photodiodes each in a different one of the three interleaved sub-arrays, and wherein the determined thickness of ~~the said~~ at least one insulating layer above each ~~respective photodiode of the three photodiodes~~ the same sub-array has a different thickness to interferentially filter a different wavelength of light.

Cont'd  
C1

Please add the following new claims. }

31. (New) The array of photodiodes of claim 1, wherein each of the photodiodes of each respective sub-array has a capacitance, and wherein said at least one conductive layer of the interference filter coating the respective sub-array determines the color of light that is interferentially filtered and provided to the respective sub-array and increases the capacitance of each of the photodiodes of the respective sub-array.

32. (New) The photodiode of claim 12, wherein the photodiode has a capacitance, and wherein the electrical connection of said conductive layer to said semiconductor substrate increases the capacitance of the photodiode.

33. (New) The photodiode of claim 17, wherein the photodiode has a capacitance, and wherein said means increases the capacitance of the photodiode by electrically connecting said conductive layer to said semiconductor substrate.

34. (New) The photodiode of claim 27, wherein the photodiode has a capacitance, and wherein the electrical connection of said conductive layer to said base substrate increases the capacitance of the photodiode.

